



Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 16

LOCTITE 3513 known as 3513 (LPD-3624) 250ML JP

SDS No. : 173396
V006.3

Revision: 28.05.2015

printing date: 16.10.2018

Replaces version from: 11.08.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 3513 known as 3513 (LPD-3624) 250ML JP

Contains:

Bisphenol A Diglycidyl Ether

Bisphenol-F epichlorhydrin resin; MW<700

Neodecanoic acid, oxiranylmethyl ester

Phenol-formaldehyde polymer

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Germ cell mutagenicity	Category 2
H341 Suspected of causing genetic defects.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: Prevention

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement: Response

P302+P352 IF ON SKIN: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Bisphenol A Diglycidyl Ether 1675-54-3	216-823-5	10- 30 %	Eye Irrit. 2 H319 Skin Irrit. 2 H315 Skin Sens. 1 H317 Aquatic Chronic 2 H411
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	500-006-8 500-006-8 01-2119454392-40	20- 30 %	Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Aquatic Chronic 2 H411
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	247-979-2 01-2119431597-33	10- 30 %	Skin Sens. 1; Dermal H317 Aquatic Chronic 2 H411 Muta. 2 H341
Phenol-formaldehyde polymer 9003-35-4	500-005-2	1- 10 %	Eye Irrit. 2 H319 STOT SE 3 H335 Skin Sens. 1 H317
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	500-033-5 500-033-5 01-2119456619-26	1- 10 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Aquatic Chronic 2 H411
Phenol 108-95-2	203-632-7 01-2119471329-32	0,1- < 1 %	Muta. 2 H341 STOT RE 2 H373 Skin Corr. 1B H314 Acute Tox. 3; Dermal H311 Acute Tox. 3; Oral H301 Acute Tox. 3; Inhalation H331

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

None

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Hygiene measures:

- Good industrial hygiene practices should be observed.
- Wash hands before work breaks and after finishing work.
- Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

7.3. Specific end use(s)

Epoxy adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Phenol 108-95-2 [PHENOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Phenol 108-95-2 [PHENOL]	4	16	Short Term Exposure Limit (STEL):		EH40 WEL
Phenol 108-95-2 [PHENOL]	2	7,8	Time Weighted Average (TWA):		EH40 WEL
Phenol 108-95-2 [PHENOL]	2	8	Time Weighted Average (TWA):	Indicative	ECTLV
Phenol 108-95-2 [PHENOL]	4	16	Short Term Exposure Limit (STEL):	Indicative	ECTLV

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	aqua (freshwater)					0,003 mg/L	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	aqua (marine water)					0,0003 mg/L	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	STP					10 mg/L	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	sediment (freshwater)					0,294 mg/kg	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	sediment (marine water)					0,0294 mg/kg	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	soil					0,237 mg/kg	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	aqua (intermittent releases)					0,0254 mg/L	
2,3-Epoxypropyl neodecanoate 26761-45-5	aqua (freshwater)					3,5 µg/L	
2,3-Epoxypropyl neodecanoate 26761-45-5	aqua (marine water)					0,35 µg/L	
2,3-Epoxypropyl neodecanoate 26761-45-5	STP					50 mg/L	
2,3-Epoxypropyl neodecanoate 26761-45-5	aqua (intermittent releases)					0,035 mg/L	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	aqua (freshwater)					0,006 mg/L	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	aqua (marine water)					0,0006 mg/L	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	aqua (intermittent releases)					0,018 mg/L	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	STP					10 mg/L	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	sediment (freshwater)					0,996 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	sediment (marine water)					0,0996 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	soil					0,196 mg/kg	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	oral					11 mg/kg food	
Phenol	aqua					0,0077 mg/L	

108-95-2	(freshwater)						
Phenol 108-95-2	aqua (marine water)					0,00077 mg/L	
Phenol 108-95-2	sediment (freshwater)				0,0915 mg/kg		
Phenol 108-95-2	sediment (marine water)				0,00915 mg/kg		
Phenol 108-95-2	soil				0,136 mg/kg		
Phenol 108-95-2	aqua (intermittent releases)					0,031 mg/L	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	Workers	Dermal	Acute/short term exposure - local effects		0,0083 mg/cm2	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	Workers	Dermal	Long term exposure - systemic effects		104,15 mg/kg bw/day	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m3	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	general population	Dermal	Long term exposure - systemic effects		62,5 mg/kg bw/day	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	general population	Inhalation	Long term exposure - systemic effects		8,7 mg/m3	
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	general population	oral	Long term exposure - systemic effects		6,25 mg/kg bw/day	
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	Dermal	Long term exposure - systemic effects		1,4 mg/kg bw/day	
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	Inhalation	Long term exposure - systemic effects		1,965 mg/m3	
2,3-Epoxypropyl neodecanoate 26761-45-5	general population	Dermal	Long term exposure - systemic effects		0,7 mg/kg bw/day	
2,3-Epoxypropyl neodecanoate 26761-45-5	general population	Inhalation	Long term exposure - systemic effects		1 mg/m3	
2,3-Epoxypropyl neodecanoate 26761-45-5	general population	oral	Long term exposure - systemic effects		1,1 mg/kg bw/day	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	Dermal	Acute/short term exposure - systemic effects		8,33 mg/kg bw/day	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	Inhalation	Acute/short term exposure - systemic effects		12,25 mg/m3	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	Dermal	Long term exposure - systemic effects		8,33 mg/kg bw/day	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Workers	Inhalation	Long term exposure - systemic effects		12,25 mg/m3	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	general population	Dermal	Acute/short term exposure - systemic effects		3,571 mg/kg bw/day	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	general population	Dermal	Long term exposure - systemic effects		3,571 mg/kg bw/day	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	general population	Inhalation	Acute/short term exposure - systemic effects		0,75 mg/m3	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	general population	Inhalation	Long term exposure - systemic effects		0,75 mg/m3	

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	general population	oral	Acute/short term exposure - systemic effects		0,75 mg/kg bw/day	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	general population	oral	Long term exposure - systemic effects		0,75 mg/kg bw/day	
Phenol 108-95-2	Workers	Dermal	Long term exposure - systemic effects		1,23 mg/kg	
Phenol 108-95-2	Workers	Inhalation	Long term exposure - systemic effects		8 mg/m3	
Phenol 108-95-2	Workers	Inhalation	Acute/short term exposure - local effects		16 mg/m3	
Phenol 108-95-2	general population	Inhalation	Long term exposure - systemic effects		1,32 mg/m3	
Phenol 108-95-2	general population	Dermal	Long term exposure - systemic effects		0,4 mg/kg	
Phenol 108-95-2	general population	oral	Long term exposure - systemic effects		0,4 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:**Respiratory protection:**

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

liquid

liquid

Cream

Odour threshold

No data available / Not applicable

pH

Not applicable

Initial boiling point	No data available / Not applicable
Flash point	> 100 °C (> 212 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.
Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Protect from direct sunlight.

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Mutagenicity:

Suspected of causing genetic defects

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 420 (Acute Oral Toxicity)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	LD50	2.000 mg/kg	oral		rat	
Phenol-formaldehyde polymer 9003-35-4	LD50	4.100 mg/kg	oral		rat	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	LD50	> 2.000 mg/kg	oral		rat	

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Phenol 108-95-2	LC0		Aerosol	8 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	LD50	2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	LD50	23.000 mg/kg	dermal		rabbit	

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Phenol 108-95-2	corrosive	3 min		

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Phenol 108-95-2	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	sensitising	Mouse local lymph node assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		hamster, Chinese	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	positive	oral: gavage		mouse	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Phenol 108-95-2	positive	in vitro mammalian cell micronucleus test	with and without		

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure time Frequency of treatment	Route of application	Method
Phenol 108-95-2	not carcinogenic	mouse	male/female	103 w daily ad libitum (continuous)	oral: drinking water	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
Phenol 108-95-2	NOAEL P = 71 mg/kg NOAEL F1 = 70 mg/kg NOAEL F2 = 1.000 mg/l	two-generation study oral: drinking water		rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.
Toxic to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	LC50	3,1 mg/l	Fish		Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	1,3 mg/l	Daphnia		Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	1,6 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	EC50	1,8 mg/l	Algae	72 h		OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	NOEC	0,3 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	LC50	9,61 mg/l	Fish	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish Acute Toxicity Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	EC50	4,8 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	NOEC	1 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	LC50	1,750000 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
	LC50	1,75 mg/l	Fish	96 h	Oncorhynchus mykiss (reported as Salmo gairdneri)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	NOEC	2,4 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	9,4 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	NOEC	0,3 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Phenol 108-95-2	LC50	21,93 mg/l	Fish	14 d	Poecilia reticulata	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
	LC50	24,9 mg/l	Fish	96 h	Pimephales promelas	
Phenol 108-95-2	EC50	3,1 mg/l	Daphnia	48 h	Ceriodaphnia dubia	
Phenol 108-95-2	EC50	61,1 mg/l	Algae	96 h	Pseudokirchnerella subcapitata (reported as Selenastrum capricornutum)	

12.2. Persistence and degradability

Persistence and Biodegradability:

No data available for the product.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	-------------------------	---------------	--------

Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5		aerobic	5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	under test conditions no biodegradation observ	aerobic	7 - 8 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6		aerobic	5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Phenol 108-95-2	readily biodegradable	aerobic	62 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

Cured adhesives are immobile.

Bioaccumulative potential:

No data available for the product.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Bisphenol A Diglycidyl Ether 1675-54-3	3,84					
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	4,4				20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Phenol 108-95-2		17,5	5 h	Danio rerio (reported as Brachydanio rerio)	25 °C	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
Phenol 108-95-2	1,47				30 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Bisphenol-F epichlorhydrin resin; MW<700 9003-36-5	Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packaging group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
-----	----------------

	Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3,00 %
(1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.