



High Performance Silicone Adhesives & Sealants



Momentive Performance Materials provides leading-edge silicone technologies to help meet performance and productivity challenges in a wide range of automotive and electronic applications.

Design freedom, long term performance and productivity needs continue to drive the trend from mechanical assembly to high-speed, automated adhesion. Also, more and more components migrate to electronic solutions that need to be assembled. Momentive offers a range of fast cure silicone adhesives for high productivity assembly, as well as solutions for electronic components that provide design flexibility and long-term component reliability under harsh operating conditions.

Key Features

- Primerless adhesion to many substrates
- Fast cure
- Long term elasticity
- Non-corrosive
- One-component available
- Choice of cure systems

Typical Benefits

- Broad application
- Productivity, high outputs
- Compensate CTE mismatch
- Reduced risk for electronics
- Ease of use
- Design flexibility

Potential Applications

- Headlamp assemblies
- ECU adhesion
- Sensor adhesion
- Wire connector sealing
- HVAC systems

www.techsil.co.uk

Typical Physical Properties

(selected grades only; please contact us for material selection support)

Product	Cure (1)	System	Cure Time / Tack Free Time (3)	Color	Flowability	Feature
Addisil* 6101 adhesive sealant	AC	1 part	CT 10 min @ 125 °C	Black	Non-flowable	Fast bonding @ 125 °C
TSE322	AC	1 part	CT 30 min @ 150 °C	Light blue, Black	Flowable	Fast bonding @ T>125 °C
TSE326M-EX	AC	1 part	CT 1 hr @ 150 °C	Red	Flowable	High heat stability
TN3005	CC	1 part	TFT < 10 min @ RT	Clear, white, black	Non-flowable	Tin free/ Fast cure/ Low volatile
TN3305	CC	1 part	TFT < 10 min @ RT	Clear, white, black	Flowable	Tin free /Fast cure/ Low volatile
TN3085	CC	1 part	TFT < 10 min @ RT	White, grey	Non-flowable	Tin free/ Fast cure/ Low volatile
RTV210A / 224B	CC	2 part (10:1 w/w)	CT 15 min @ RT(2)	Black	Non-flowable	Fast bonding @ ambient

(1) AC = Addition Cure, CC = Condensation Cure

(2) After 10 - 30 minutes cure at RT the bond strength is usually sufficient to allow part handling - full cure obtained after 1-3 days at ambient

(3) CT = Cure Time, TFT = Tack Free Time

Typical data are average data and are not to be used as or to develop specifications.

*Addisil is a trademark of Momentive Performance Materials GmbH.

MOMENTIVE™
 authorized distributor
 +44 1789 773232
 sales@techsil.co.uk
 www.techsil.co.uk

TECHSIL®
 Unit 34 Bidavon Industrial
 Estate
 Waterloo Road
 Bidford on Avon
 Warwickshire
 B50 4JN, UK

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (I) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (II) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc. Copyright 2016, Momentive Performance Materials Inc. All rights reserved.

11/2016