



## Thermal Management Silicones



Momentive Performance Materials provides leading-edge silicone technologies to help meet performance and productivity challenges in a wide range of automotive and electronic applications.

Long term, reliable protection of sensitive electronic components is essential to many applications today. Increasingly small systems and rising circuit densities have resulted in higher operating temperatures, and driven demand for high-performance solutions for heat dissipation.

### Key Features

- Good mechanical properties
- Property stability under harsh operating conditions
- Low thermal resistance at thin bond lines
- Very fast cure

### Typical Benefits

- Reliability
- Compensate CTE mismatch
- Extended component life
- High productivity

### Potential Applications

- Power modules
- Sensors
- Board assemblies
- LED assemblies

## Thermal Management Materials Typical Properties

(selected grades only; please contact us for material selection support)

Product	System (1)	Type	Cure Time(2)	Thermal Cond. (W/m·K)	Color	Flowability	Feature
TIG210BX	TIG	Grease	n.a.	2.1	Grey	Non-flowable	Low bleed grease
TIG830SP	TIG	Grease	n.a.	4.1	Grey	Non-flowable	Screen printable grease
TIA216G	AC, 2K	Soft rubber	30 min @ 70 °C	1.6	Grey	Flowable	8 Pa.s; tacky adhesion; UL94-V0, UL RTI 150 °C
TIA222G	AC, 2K	Soft rubber	30 min @ 70 °C	2.2	Grey	Flowable	20 Pa.s; tacky adhesion; UL94-V0
TIA225GF	AC, 2K	Gap Filler	30 min @ 70 °C	2.5	Grey	Non-flowable	Soft stress-absorbing rubber; can cure at room temp
TSE3281-G	AC, 1K	Adhesive	30 min @ 150 °C	1.7	Grey	Flowable	Adhesive
XE13-C1862PT	AC, 1K	Adhesive	30 min @ 150 °C	2.4	Grey	Flowable	High elongation; pin transferable
XE11-B5320	CC, 1K	Adhesive	TFT 5 min @ RT	1.3	White	Non-flowable	Adhesion at RT
TIA0220	CC, 1K	Adhesive	TFT 10 min @ RT	2.2	Grey	Semi-flowable	Adhesion at RT; high thermal conductivity
TIA0260	CC, 1K	Adhesive	TFT 10 min @ RT	2.6	Grey	Semi-flowable	Adhesion at RT; high thermal conductivity, UL94-V0
TIA350R	AC, 1K	Adhesive	30min @ 120 °C	3.5	Grey	Semi-flowable	High thermal conductivity

(1) AC = Addition Cure / CC = Condensation Cure / TIG = Thermal Interface Grease (2) TFT = Tack Free Time

Typical data are average data and are not to be used as or to develop specifications.

**MOMENTIVE™**

authorized distributor

+44 1789 773232

sales@techsil.co.uk

www.techsil.co.uk

**TECHSIL®**

Unit 34 Bidavon Industrial  
Estate  
Waterloo Road  
Bidford on Avon  
Warwickshire  
B50 4JN, UK

#### Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

#### Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at [www.momentive.com](http://www.momentive.com) or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

#### Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

#### DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.  
Copyright 2016, Momentive Performance Materials Inc. All rights reserved.

03/2017